

dm-folien GmbH • Markwiesenstraße 33 • 72770 Reutlingen

TECHNICAL DATA SHEET

APPLICATION: PACKAGING TAPE - COLORED - ACRYLIC

Article	Backing Type	Backing Thickness (µm)	Adhesive Type	Total Thickness (µm)	Adhesion to Steel (N/cm) (AFERA 5001)	Tensile Strength (N/cm) (AFERA 5004)	Elongation at break (%) (AFERA 5004)
A28	BOPP	28	Acrylic (Water Based)	48	2,2	40	160
Tolerance				+/- 5%	+/- 10%	+/- 10%	+/- 15%

Adhesive tape: PP5

Please follow your local disposal guidelines

Stocking time

We recommend to use the product within 6 months from the delivery.

Stocking conditions

Store the product in a clean dry place, at a temperature between 15°C and 25°C.
The product must be stored protected from dust, humidity and direct sun exposure.
It must be stored horizontally and kept in the original packaging.

Use

If the storage temperature has been different from what suggested, bring the tape back to that temperature before application.
Before applying the tape, remove any trace of dust or any other dirty from the application surface. Press the tape down thoroughly for a perfect and time lasting adherence.

Important:

The mentioned data stem from an average analysis carried out on our standard production and may undergo unexpected changes. Therefore they are not binding for our company.

Cod. Doc. 074.01 Liv. rev. 11 Data 01/06/2023
Ver. 3 data emissione 15/01/2021